Terms in CAPS = Softkey label. Terms in [] = option to be selected. NEXT* = Possible multiple presses. Varies with installed equipment.

Flight Functions (from PFD screen)

Change Altimeter Setting: Turn Right Knob to adjust. Press knob to set.

Heading Bug: Turn Left Knob to adjust.

Altitude Bug: Press Right Knob > Turn knob to adjust > Press to set.

Dim Screen: Press Left Knob > Turn knob to adjust > Press to set.

PFD Display Options

Show PFD, MAP or Engine: Press PFD, MAP or ENG softkey

Show HSI/Change PFD Screen View: Press PFD softkey repeatedly.

Disable PFD View Options: NEXT* > PFD LOCK [ON]

Show FLIR: NEXT* > VIDEO [choose OVRL or FULL]

PFD Terrain Warning Colors: NEXT* > SV [TERRAIN]

Engine/Systems Display Features

Reset Fuel Quantity: From ENG page > Press Left Knob > Turn to select preset quantity -OR- Highlight ADJ > Press knob > Turn knob to enter custom quantity.

Display Leaning Functions: From ENG page > LEAN [LEAN]

Change Data Display on ENG Page: (From ENG) > NEXT > DATA [choose]

Set Time Frame for EGT/CHT Graphs: (From ENG) > Press Right Knob [TIME] > Turn knob to set number of seconds

Map, Flight Plans & Waypoints

Zoom Map: Press Left Knob > Turn knob

Change Map Format/Layout: Press MAP softkey repeatedly.

View Radar, Terrain, Winds: (From MAP) > SHOW [choose]

View Winds Aloft: (From MAP) > NEXT* > WINDS > UP/DOWN chngs alt.

Show Fixes & Intersections: (From MAP) > NEXT* > FIX [choose]

View Off-Screen Waypoints: (From MAP) > NEXT* > SLEW

Show Nearest: (From MAP)> NEXT* > NEAR [choose]

Direct-To: (From MAP) > FLIGHT PLAN > → > use letter keys > ENTER

Direct-To from MAP: Press Right Knob > Turn knob to select waypoint> → Press Right Knob to enter

Multi-Leg Flight Plan: (From MAP) > NEXT* > FLIGHT PLAN > SEQ MODE > ADD > Use letter keys to enter waypoints. Press Right Knob [NEXT] to move cursor. Turn/Press Right Knob [ENTER]. Repeat until all waypoints are entered. EXIT to activate flight plan.

Activate Leg: Turn Right Knob to highlight last waypoint of leg. Press SET LEG to activate leg.

Go Direct to a waypoint in a flight plan: Highlight waypoint. Press GO DIRECT. EFIS skips waypoints in between, then resumes flight plan.

View Details of waypoint on Flight Plan Screen: Turn Right Knob to highlight waypoint in list. Press RIGHT KNOB twice.

View Details of anything on MAP Screen: Press Right Knob. Rotate knob to highlight item on map. Press WPT DETAILS softkey. *Shortcut:* Note data box on MAP screen for highlighted waypoints.

Navigation

Select NAV Source: (From PFD) > GPS or NAV [Choose from the GPS and NAV (VHF radios) wired into the EFIS.]

Display VOR radial or Localizer on HSI or CDI: Enter frequency into connected VHF radio. Press PFD > NAV to display on CDI. Press PFD repeatedly to bring up split screen HSI view.

Tune VOR OBS Course on HSI (PFD split screen): Turn Right Knob.

Tune VOR OBS Course on CDI (PFD full screen): (From MAP) > Turn Right Knob.

Approach Tasks

Load Synthetic Approach: Airport must be the active GPS waypoint. (From PFD) > NEXT* > SAP [ARM] > EXIT. Turn & press Left Knob to select runway. Press EXECUTE when ready to intercept course.

View Loaded Approach Plate: (From MAP) > NEXT* > PLATE

Load Approach Plate: WPT DETAILS page > PLATE > Turn Right Knob to select approach. Press VIEW. (Requires approach plates on USB stick)

Set Approach Altitudes: (From PFD) > NEXT * > SET DA -or- SET MISSED ALT -or- SET PRESET ALT. Turn Right Knob to set altitude > Press Knob to enter. WARNING: DA is advisory only. A/P does not level off at DA. Repeat to SET MISSED ALT (missed approach holding altitude).

Missed Approach (autopilot): Press MISSED softkey to climb at runway heading ground track to preset MISSED (holding) altitude.

Execute Approach (autopilot): Press yellow EXECUTE softkey when cleared for approach to enable autopilot capture of approach course.

Basic Autopilot Controls

Engage: Turn on external switch servo power and ENGAGE/ DISENGAGE switch. A/P should hold present pitch and bank. Press red S&L HOLD ALT & HDG for emergency straight & level flight. Press red 180° ALT HLD for an emergency 180° level turn to escape IMC.

Heading Mode: Set heading bug. (From PFD) > NAV MODE [NAV]. Press Right Knob > LAT A/P [HDG]

Track GPS: Set up in HDG mode. Enter & activate flight plan or direct-to. (From PFD) > Press Right Knob > LAT A/P [ENAV].

Track VOR/LOC: Set up in HDG mode. Enter frequency into connected VHF radio. Tune OBS Course. (From PFD) > NAV MODE [ENAV]. (From PFD) > Press Right Knob > LAT A/P [ENAV]

Change altitude: (From PFD) > Press Right Knob > Turn knob to set Altitude Bug. Press RIGHT KNOB then SET CLIMB IAS/SET DESCENT RATE to climb or descend at the preset rate -OR- turn RIGHT KNOB to set custom speed/rate. Push RIGHT KNOB to activate climb/descent.

Show Flight Director: Press Right Knob twice > FLT DIR [ON]

Access Setup Menu: NEXT* > SET MENU

Miscellaneous Features

Record a Demo File to USB Stick (manual data logging): NEXT* > DEMO (configure settings in Set Menu > General Setup > DEMO Settings)

(Training Note) Configure Softkey Timeout: Setup Menu > General Setup > Initial Menu Timeout and Used Menu Timeout



Horizon

Quick-Reference
Pilot Card Rev. A