

**Model 2000G**  
**ENGINE INFORMATION SYSTEM**  
**With GPS Interface**

---



**Grand Rapids Technologies Incorporated**  
**3133 Madison Ave SE**  
**Wyoming, MI 49548**

Rev 05/09/01

# Operating Instructions for the EIS Model 2000PP

The Model 2000 is specifically designed for the powered-parachute type aircraft, requires very little input from the pilot.

## Before using the Model 2000 for the first time:

1. Set the units for temperature, altitude, and fuel quantity (if used) as desired. The instruments are set at the factory to Fahrenheit, Feet and Gallons for temperature, altitude, and fuel respectively.
2. Read the section on “Automatic Altimeter” operation. Set this as desired.
3. Engine limits are pre-set at the factory. You may review these limits, and change them at any time if you desire.
4. All settings in the instrument may be set back to the initial factory settings by holding the right button (“Display”) when turning on the instrument.

## Before Each Flight:

If the altimeter is operated in the Manual mode, set the altimeter appropriately. If the altimeter is set to the automatic mode, no action is required.

## Detailed Description of the Features:

### Automatic/Manual Altimeter Setting.

The altimeter can be set manually by the pilot, or automatically the by the instrument. This option is selected on the “SET LIMITS” pages.

### Automatic Altimeter Operation -

In this mode the altimeter will automatically be set to zero at 45 and 75 seconds after the instrument is turned on, if the engine is running and has not exceeded 4100 RPM. If the RPM goes above 4100, the instrument assumes the airplane is in the air, thus does not alter the altimeter setting.

The intent of this logic is to allow the instrument to automatically zero the altimeter when the engine is being warmed up on the ground, but hopefully not cause the instrument to reset the altimeter when the instrument is turned on and off in the air. The automatic mode of the altimeter should not be used when:

- You wish to set the altimeter to the airport’s elevation. This is often done when flying to another airport, especially when the airports are at different elevations.
- If you anticipate turning off the instrument in flight, and then turning it back on when the engine RPM is below 4100. This could be the case when stopping the engine in flight, and restarting.

### Manual Altimeter Operation –

Use the “SET LIMITS” pages to set the altimeter as desired.

### Flight Timer

The flight timer shows you how long your flight has lasted. It resets at power up, and starts counting when the engine is running (based on the tachometer). It displays the previous flight time until the current flight time reaches 3 minutes, allowing you to easily recall the length of the previous flight. A warning can be set when the timer exceeds your preset limit to remind you to check your fuel.

### Checklist

The checklist is displayed immediately upon turning the instrument on. The “Next” button is used to scroll through each of the checklist pages. The checklist ends when any of the following occurs.

- All of the checklist pages have been reviewed.
- The “Display” button is pressed. This allows you to easily bypass the checklist.
- The engine RPM goes over 4100, indicating the airplane is probably airborne.

**Favorite Page**

The instrument will automatically select your favorite page when the checklist is ended, or the right button is double-clicked, or when leaving the “Set Pages”. Your favorite display page is entered under the “DISPLAY” setting in the “Set Limits” pages. It is the last setting on these pages.

**Combo Screen On-Screen Labels**

Pressing the right button (“Display”) when on a combination page (that is, a page with no labels), will replace the numeric data with labels to identify the data. Releasing the button returns the numeric data to the page.

Double-clicking the “Display” button immediately takes you to your favorite page. Normally a combination page is used as your favorite.

**GPS Page**

The GPS page gives you easy-to-read and easy-to-understand steering information to get you home. It also provides groundspeed, as well as the distance and magnetic bearing to home. This function requires the connection of a GPS to the EIS to perform these functions. Using the GPS page provided on the EIS has several advantages over that of a stand-alone GPS, namely:


- Automatic Operation – A GPS requires the creation of a waypoint for each location you fly from, and also requires that you manually select the correct waypoint as the “Goto” in order to get steering information to it. The EIS does this automatically.
- Large, Readable Display – The EIS display is much larger and more easily read than any of the low-cost GPS units available today.
- Easy-to-Understand Steering – All handheld GPS receivers reviewed to date provide steering information that is sometimes invalid, and often hard to interpret. The EIS provides simple steering information, and provides it only when it is valid.
- Convenient Grouping of Information – The GPS pages shows all relevant GPS data, as well as altitude and tachometer on one screen. (Although engine temperatures are not shown, they are being monitored by the EIS alarms.)

**Saving your Home Position**

At power-up, the EIS will determine if you are on the ground. If you are, and the GPS is providing data to the EIS, it will determine if you are at the same location you flew from last time. If the EIS determines you are at a new location, it will prompt you to see if you would like to save this as your new home position. If you are at the same place you flew from your last flight, it will not issue this prompt.



If valid GPS position data is lost, the No/Yes prompt will be replaced with dashes, indicating no position is available for saving as your home position.



Normally, you will use the “Up” or “Down” button to select “Yes” and then press the right button to update your home position. Selecting “No” will retain the last home position, and is normally done only when on a cross-country flight. This page can also be manually accessed on the “Set Limits” pages, to allow you to save the current position as your home position at any time.

Note: The EIS assumes you are on the ground if the engine RPM has not exceeded 4100 RPM since the EIS was turned on, and the GPS indicates you are not moving.

## Using the GPS Page

The GPS page is described in detail in figure 2. This page provide steering information to direct you to your home position, as well as RPM, altitude, groundspeed, distance and bearing to home. When data can not be calculated, or is unavaliabe, it will be replaced with dashes to indicate that no valid data is available.

### Connecting a GPS and Setting up the GPS Function.

1. Only 2 electrical connections are required to a GPS. These are the serial data output line and ground. Refer to figure 2 for an illustration of how these connections are made.
2. Go to the “Configuration Set Pages” and make the following selections: (See the section “Configuration Set Pages” for more details on how this is done.)
  - GPS Page - ON
  - GPS Baud - 4800
  - GPS Units – Miles or Kilometers, as desired.
3. Turn on the GPS. Refer to its user’s manual to select NMEA 0183 serial out on. Select a baud rate of 4800. If necessary, make any selection required to enable the GPRMC output sentence. (Most GPS receivers will transmit the GPRMC sentence automatically when the NMEA 0183 selection is made.)
4. Verify the EIS is receiving GPS data by checking the GPS page on the EIS. If data is being received, the “X” on this screen will disappear. When the GPS locks onto the satellites, a groundspeed of 0 will be displayed on the EIS. (Note: Magellen brand GPS receivers do not activate the data output until they have locked onto satellites and are able to provide a valid position. Garmin brand GPS receivers typically activate data output as soon as they are turned on, even before any position data is available.)

If no data is received by the EIS, double check your electrical connections, verify the GPS setup to transmit NMEA 0183 at 4800 baud, and verify the EIS is set to a baud rate of 4800. A fluctuating voltage of a couple of volts can be measured between the GPS serial output line and ground to verify it is providing data output.

### Peak Recording

The EIS records the peaks (maximums) for 9 parameters during the flight. The recording of these items begins when 3 minutes has elapsed on the flight timer, at which time the peaks from the last flight are erased.

Since the peaks are recorded in non-volatile memory, the EIS is able to show you the peaks from the previous flight, even if the EIS has been turned off since the end of the last flight. (These peaks will not be erased until 3 minutes into the next flight.) This can be very useful for evaluating the highest RPM generated by your engine, peak engine temperatures, as well as your maximum altitude and your maximum distance from your home position.

The peaks that are recorded are as follows:

- Tachometer
- Cylinder Head Temperature #1 & #2
- Exhaust Gas Temperature #1 & #2
- Coolant Temperature
- Voltmeter
- Altimeter
- GPS Range (from your home position)

To view the peaks, select the “Set Limits” pages, and page down to the “Show Peaks” page. Use the UP/DOWN to select “YES”. Press and hold the right button to leave the set pages. The peak values for the above items will replace their current values on the various display pages. The EIS will alternately flash the symbol “PK” and the peak data to identify the peaks.

The “Show Peaks” function can be turned off by returning to the “Show Peaks” page and selecting “NO”. This function is also automatically turned off at power-up, or whenever the RPM exceeds 4100. The “Show Peaks” function is disabled when the RPM is above 4100.

## Warning System Operation

The alarm system is the most important part of the system. It allows you to enjoy flying without the need to constantly monitor your instrument. Damaging engine conditions are made immediately obvious.

All alarms cause the warning light to flash, and the page to change automatically to a labeled screen which includes the out-of-limit parameter. The offending parameter is flashed on the display, along with the warning light until the problem goes away, or until it is acknowledged by pressing the “Next/Ack” button. Acknowledged alarms cause the warning light to stay on steady until the condition ends, and does not inhibit other alarms.

## Set Limit Pages

The settings on these pages are accessed by pressing the left and center buttons together. This will immediately bring up the set pages, displaying each item listed, one at a time. While on the set pages, the bottom row of the display will show “UP Down Next”, indicating the function of the buttons while on these pages. As such, the left and center buttons allow you to change the setting, and the right button takes you to successive settings. To leave these pages, repeatedly press the right button, or press and hold the right button, until the normal display pages return. The items that can be set on these pages are, in order, as follows:

- **Contrast** defaults to the best setting at power-up. It may be altered if desired to enhance readability.
- **Alt-Set** allow you to select Auto or Manual for the altimeter setting function.
- **Alt** shows the current altimeter setting. Altitude is manually set here.
- **New Home Pos?** This setting is only available if the GPS page is turned on. Selecting “Yes” and pressing the right button stores the current position as your home position. Dashes will be displayed when no valid GPS position has been received in the last 60 seconds.
- **Show Peaks** allows you to display the peak values in place of the current values on the various display pages. This function is inhibited while the RPM is greater than 4100. See the “Show Peaks” section for more information.
- **Max Timer** gives you the maximum time before the flight timer will issue an alarm. The limit is entered in minutes. If you exceed this limit, it can be increased easily in flight.
- **Max Cool** is the maximum coolant temperature.
- **Max RPM** is the maximum RPM. This limit is set in 30 RPM increments.
- **Min Fuel** applies to the optional fuel level input.
- **Max Volt** is used to warn of overcharging due to a failed regulator. A good limit for this is 15.0 volts. If a battery is not used, this alarm is not required.
- **Min Volt** is used to warn of battery discharging. A good setting for this is 12.0 - 12.8 volts.
- **Max EGT** is a very critical alarm, as high EGT can destroy an engine in seconds to minutes. It reflects the fuel/air mixture being burned by the engine. A typical limit is 1200-1250 degrees F.
- **Max CHT** warns of inadequate cooling.
- **Display** is used to enter your favorite display page.

## Configuration Set Pages

These pages contain information that configures the instrument to your engine, and selects various options.. These pages are accessed by pressing and holding the **right** and center buttons for several seconds, until the bottom row of the screen displays “Up Down Next”. While on the configuration set pages, the bottom row of the display will show “UP Down Next”, indicating the function of the buttons while on these pages. As such, the left and center buttons allow you to change the setting, and the right button takes you to successive settings. To leave these pages, repeatedly press the right button, or press and hold the right button, until the normal display pages return. The items that can be set on these pages are, in order, as follows:

- **Fuel , Temp. and Altitude** show the units they are using. The units for the vertical speed (climb rate) indicator are feet per minute (in increment of 100 feet per minute), or meters per second, corresponding to the selection for the altimeter.
- **GPS\_Page** – When “On” enables the GPS page. This page appears after the second combination page. See the section “GPS Page” for a complete description.
- **GPS\_Units** – Selects whether miles or kilometers will be used as the units on the GPS pages. Has no effect if GPS\_Page is off.
- **GPS\_Baud** – Selects the baud rate for receiving data from the GPS. Most GPS receivers transmit data at 4800 baud, and this setting should be used.
- **EGT\_Toggle** – When “Off”, the highest EGT is displayed on combination screen 1. When “On”, this display will toggle between the two EGTs every 2 seconds, allowing you to observe both EGTs without switching pages.

- **CHT\_Toggle** – When “Off”, the highest CHT is displayed on combination screen 1. When “On”, this display will toggle between the two CHTs every 2 seconds, allowing you to observe both CHTs without switching pages.
- **Combo\_Page** – Selects whether coolant temperature (Cool) or outside air temperature (OAT) is displayed on the combination pages. The OAT selection is useful when coolant temperature is not being monitored.
- **TachP/R** - Indicates the number of pulses per revolution of the engine for tachometer sensing. Rotax CDI engines require a setting of 6. The Rotax 912 requires a setting of 1.
- **Fuel-SF, Fuel-Off, FuelSens** - Fuel level input scaling. Normal settings are 5, 0, and Forward, respectively. When using a Princeton Electronics fuel level probe, set the Fuel-SF to half of the desired full tank reading. (For example, if you want to display the fuel level as 0-100%, set the Fuel-SF to 50).

## Messages at Power-Up

- ◆ **Non Rotax-Tach Setting** – This indicates the TachP/R setting is not standard for a Rotax engine. This is a reminder that it may be set wrong. The instrument will not change the TachP/R setting however.
- ◆ **Limits Reset!** – This indicates that a limit may have been altered unintentionally. The instrument will reset all limits to the initial factory setting.

Last printed 9/3/2013 1:34:00 PM